



Home Tips®



• CHRISTIAN BUILDING INSPECTORS, INC., 3697 HABERSHAM LANE, DULUTH, GEORGIA 30096, 770-849-0920 • JANUARY 2004 •

Q & A

Pressure -Treated Wood: The Next Generation

The EPA is banning CCA lumber. The replacements are safer, but they may change how you build a deck.

Nearly 40 million pounds of arsenic is used in this country every year, and most of it goes into the pressure-treated wood that we use to build decks and playgrounds. But that all changes January 1, 2004. The Environmental Protection Agency (EPA) is banning chromated copper arsenate (CCA) as a preservative for wood intended for residential use (except for the lumber that is used in permanent wood foundations). CCA-treated lumber will still be available for industrial and agricultural use, however.

By the way, there's no need to panic about existing CCA treated structures. The EPA says that they're fine. But if



Don't panic
about the CCA
swing set in
your backyard

you're nervous about the chances of leaching chromium and arsenic, you can make your deck or swing set safer by coating it with an oil-based penetrating stain every couple of years.

Taking CCA's place as a preservative are two waterborne compounds: alkaline copper quat (ACQ types B and D) and copper azole (CBA-A, CA-B). Sold under the trade names Preserve, Nature Wood, and Natural Select, they have been used around the world for up to 15 years. These EPA-approved low-toxicity

pesticides resist bugs, mold, and rot as effectively as CCA.

More copper makes the wood more expensive

To make the new preservatives effective, their copper content has been boosted substantially—from around 18% to 96% in some cases. Because ACQ and copper azole contain so much more copper, you can expect to pay from 15% to 35% more than you paid for CCA lumber. The cost varies

because the amount of chemical treatment varies. CCA wasn't that expensive, so most CCA lumber was given a maximum dose of preservatives and rated for ground contact. To keep down the cost of the new pressure-treated wood, manufacturers will produce different levels of protection (chemical-retention levels) for different end uses. End-use categories will be marked on the tags stapled to the end of the board, but in general, they'll be determined by the dimension of the lumber itself. The lowest chemical-retention level will be for 5/4 stock, or decking. One level higher will be 2x lumber, or above ground. Ground contact will be 4x and 6x lumber, and other stock will be treated for permanent wood foundations (PWF, or structural members).

Although most of the time this system of categorizing chemical-retention levels will jibe with the actual end use, a reasonable potential exists for accidental misuse. You need to make sure you're using ground-contact lumber if that's what you need.

Use corrosion-resistant nails and joist hangers

Unfortunately, boosting the copper content in lumber not only makes the new pressure-treated wood more expensive than the old, but it also makes the new stuff significantly more corrosive—5 times more than common steel, according to American Wood Preservers Association (AWPA) test results.

Most people already know that they should use corrosion-resistant nails, screws, and connectors when they're building with pressure-treated wood. But now the stakes are higher. Due to the high risk of galvanic reaction between the copper-impregnated wood and any dissimilar metals, fasteners and flashings should be stainless steel and copper whenever possible. At the very least, you need to use better grades of galvanized fasteners. Unfortunately, the fastener grades aren't always marked on the boxes of nails and screws.

Electrogalvanized stock is rated with a class scale that ranges from 5 to 110. Hot-dipped galvanization ratings are based on the actual weight of the coating. For example, a G-60 rating means that there's 0.60 oz. of zinc per sq. ft. of metal.

The G-60 and G-90 hot-dipped coatings are what we've been using until now. But engineers suggest stepping up to the heavier G-185 coatings for hot-dipped galvanized products, and they recommend class ratings of 40 or above when using electrogalvanized fasteners, such as expansion bolts.

Currently, G-185 is the best galvanized protection that you can buy. Simpson's ZMax line and USP Structural Connectors' Triple Zinc line both are rated at G-185. As for nails and screws, many of the composite coatings that are currently available are still good for the new treatments (see www.osmose.com to read about fastener recommendations),

but you should verify this by carefully reading the label.

Perhaps the most important point to keep in mind relating to copper— based wood treatments and galvanic corrosion is to avoid aluminum flashings altogether. Aluminum corrodes quickly in the presence of high copper concentrations.

You are the weakest link

The weak links in the system with the new treatments are instances where there's a significant chance of using the wrong fastener or flashing. Deck flashing will have to be either galvanized or copper. Pressure-treated bottom plates in slab-on-grade construction also offer weak links. Cumulative effects of corrosion could be catastrophic in tornado and hurricane zones. Will production-framing crews meticulously switch to galvanized nails when nailing studs and sheathing to the bottom plate? And what about foundation anchor bolts, which attach pressure-treated mudsills to basement walls? Galvanized versions are made, but they aren't commonly available.

Nails for powder-actuated tools and retrofit expansion bolts have a zinc plating, but their electrogalvanizing may need to be boosted to a higher class rating. Engineers at Ramset-Redhead say it's too early for their corrosion-test results to show a trend.

The wood still needs to dry before you can stain it

Most water repellents can be applied immediately to the new pressure-treated wood, and some manufacturers offer a water-repellent treatment as an upgrade. But manufacturers still recommend an additional level of protection. The wood preservers' group suggests waiting for the lumber to dry before applying an oil-based semitransparent stain to the new varieties of pressure-treated lumber. How long you should wait before applying the stain varies depending on where you live. In New Mexico, you probably should wait for six weeks; in New Orleans, six months would be a more preferable length of time.

Editor's Note: The type of treatment showing up in the Atlanta area is ACQ and it comes in two concentrations. Lumber for above ground use is .25 pcf and lumber for ground contact (for wood post) of .40 pcf. Lowe's and Home Depot have both the new ACQ and the old CCA lumber and will be selling CCA until they sell what is in stock. You can check the tags on the end of the lumber to see if it has CCA or ACQ. Both have information on the new fastener requirements and a list of manufacturer's and products to use.

Daniel S. Morrison Fine Homebuilding.

December 2003/January 2004

If you have a question, change of address, comment, home tip or would like to send *Home Tips* to your clients, send your letter to *Home Tips*, Christian Building Inspectors, Inc., 3697 Habersham Lane, Duluth, Georgia, 30096-6111. You can also E-Mail your questions to us at rodharrison@christianbuildinginspectors.com. We reserve the right to edit questions for length.

Quote Of The Month

" A RICH PERSON IS NOT ONE WHO HAS THE MOST, BUT NEEDS THE LEAST."

INTERVIEW WITH GOD

A Tip Of The Hat To:

Pat Graves
Prudential Atlanta Realty
4390 Pleasant Hill Road
Duluth, Georgia 30096



Thank You

• CHRISTIAN BUILDING INSPECTORS, INC. •

• Member: ASHI, GAHI, MAIA, ICC •

• ICC CODE CERTIFIED CABO ONE & TWO FAMILY DWELLING INSPECTOR NO. 1619 •

• Fully Insured With E&O, Liability and Worker's Compensation Insurance •

• Office: 1-888-257-0365 or 770-849-0920, Fax 770-849-0540, Digital Pager 770-890-4503 •

• Web Page: www.christianbuildinginspectors.com Email: rodharrison@christianbuildinginspectors.com •



- Site
- Drainage
- Foundations
- Floor Slabs
- Crawl Spaces
- Basements
- Structural
- Interior
- Exterior
- Appliances
- Ventilation
- Electrical
- Plumbing
- Heating
- Air Conditioning
- Attic
- Roofing
- Radon
- New Homes
- Warranty
- Construction